

market@vzor.nnov.ru www.vzornn.com

Portable Dissolved Oxygen meter MARK-302T

MARK-302T is a portable meter for measuring dissolved oxygen concentration and temperature for aqueous mediums including deairated ones (low-level range).

Features

- > Automatic barometric pressure compensation
- > Automatic temperature compensation
- > Automatic one-point calibration in air
- > Splashproof front panel
- Long-lived probe
- > Low-power: battery lifespan up to 2000 hours of work

Measuring range

Specification

DO concentration, ppm	0,000 20	0,001	±(0,003 + 4% of value)	
Temperature, °C	0 50*	0,1	±0,3	
Ambient overpressure:	0,5 bar			
Dimensions: instrument o	→ Included			
sensor	Register of approv			
Weight of instrument only	→ Has the			

Resolution

Power supplytwo AA-type elements

What's included: DO probe with 2m cable, flow-through chamber, electrolyte, consumables kit, two AA batteries, operation manual

- ☆ Included into Russian Federation State Register of approved measuring instruments
- → Has the License of Russian Federation Federal Inspectorate of ecologic, technical and nuclear for use in power plants applications
- ☆ Certificated to electromagnetic compatibility
 - ☆ Warranty 12 months

Order scl	heme Porta	ble Dissol	lved Oxyge	n meter
-----------	-------------------	------------	------------	---------

MARK-302T- 0

Accuracy

0

^{*}automatic temperature compensation range